

CS75i



- patented 75scfm oil/water separator

“The industry-leading experience of the separator design team is clear to see in every detail. It’s exactly right”



The STELSEP® CS75i is a completely new concept incorporating many features and customer benefits in a single package for the treatment of condensate from any oil lubricated air compressor delivering up to 75cfm at <232 psi

- Quick and secure installation with wall and floor mount options in the box
- **10-year warranty** on CS75i body. See the website for full details
- **No tools required for servicing.** Simply rotate the lid and lift off to remove the moulded cartridge and clip in a new one
- **‘No-Spray’** CS75i has 3 levels of protection, ensuring that condensate can’t exit the de-pressurising vents
- **Visual time-in-service indication** is fully incorporated into the design
- **Up to 4000 hours service life**

Even users of small compressed air systems must comply with laws regarding pollution caused by the discharge of any untreated compressor condensate.

In a full year of operation, even a properly maintained 15 H.P. compressor could cause over 2000 gallons of condensate to form - which could contain up to 2 gallons of oil.

That’s enough oil to cover and de-oxygenate

several hectares of water, causing loss of plant and animal life. Such a concentration also inhibits the operation of waste water processing plants.

You can have condensate removed from site by a licensed contractor, but it’s easier and less expensive to treat it on site. Ask your air compressor service company to install a STELSEP® separator and be sure you meet your legal and environmental targets

STELSEP

manufacturer and supplier of condensate management and air treatment products

CS75i - 75scfm oil/water separator




Installation summary

CS75i can be attached to either wall or floor using either of the supplied fixings.

Due to its very compact size, CS75 should always be used in conjunction with one or other of the supplied fixings.

Always use auto-drains; set any timed drains to open for the shortest period

Order **STELSEP®** part no. **CS75SK** from your service company for replacement filter cartridges



General Specification

weights and dimensions are approximate

Dims (in)	Height	Width	Depth	Weight
CS75	11.4	7.1	7.5	3.1lb
CS75 Boxed	11.8	7.9	7.9	3.5 lb

Inlet: 1/4" push fit	Outlet: 3/8" push fit with adaptor to larger
--------------------------------	--

MATERIAL:
All moulded parts PE
Filter medium processed polypropylene

Max capacity of air system - 75cfm @ 16bar
Never use cartridge longer than 24 months



Time In Service (T I S) indicator

Clipped into the lid, it gives guidance regarding the need to observe and/or service the unit.

A new T I S is supplied with every replacement service kit

Guide to maximum cartridge life

in a normal well-maintained compressor system using mineral or mineral-based lubricants

Annual Hours Run	System air delivery - cfm		
	40	60	75
2000	24 months	21 months	18 months
4000	18 months	15 months	12 months
8000	12 months	9 months	6 months

What's in the box?

Outer body & lid with service cartridge and foam disc fully assembled.

Wall-mount plate, optional floor standing cup (use either mount), T.I.S. indicator, polybag



STELSEP®, PO Box 12127, Scottsdale AZ, 85267

tel: 602-741-7970 e: info@stelsep.com www.stelsep.com